

# K-FI AK KOH PC-BEHAE SCHUTZK HANSA

Activated carbon filters



Ieejas spiediens  
0 - 16 bar  
Temperatūras diapazons  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P2 = 6 bar and pressure drop  $\Delta p = 0.5$  bar  
Aizsarggrozs  
Polyamide  
Filtra elements  
Activated carbon  
Korpuss  
Material: Grivory® (PA 66)  
Pieslēguma vītne  
Material: Die-cast zinc  
Tvertne  
Polycarbonate (with bayonet lock)  
Atlikusi eļļa  
0.005 mg/m<sup>3</sup>, class 0 acc. to DIN ISO 8573-1  
Caurplūdes vērtības mērijums  
At P2 = 6 bar and pressure drop  $\Delta p = 0.5$  bar

## Apraksts

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.<br>Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m<sup>3</sup> from compressed air and gases.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 10 41	G 1/4	500	52.0	157.0 mm	34.0
K- 07 25 10 42	G 3/8	500	52.0	157.0 mm	34.0
K- 07 25 10 43	G 3/8	1600	63.0	183.0 mm	42.5
K- 07 25 10 44	G 1/2	1600	63.0	183.0 mm	42.5
K- 07 25 10 23	G 3/4	3000	85.0	240.5 mm	58.0
K- 07 25 10 24	G 1	3000	85.0	240.5 mm	58.0