

K-FI AK KOH PC-BEHAE SCHUTZK HANSA

Activated carbon filters



Ieejas spiediens
0 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar
Aizsarggrozs
Polyamide
Filtra elements
Activated carbon
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock)
Atlikusi eļļa
0.005 mg/m³, class 0 acc. to DIN ISO 8573-1
Caurplūdes vērtības mērijums
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar

Apraksts

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.
Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm |
|----------------|--------|-------------------------|---------|----------|---------|
| K- 07 25 10 41 | G 1/4 | 500 | 52.0 | 157.0 mm | 34.0 |
| K- 07 25 10 42 | G 3/8 | 500 | 52.0 | 157.0 mm | 34.0 |
| K- 07 25 10 43 | G 3/8 | 1600 | 63.0 | 183.0 mm | 42.5 |
| K- 07 25 10 44 | G 1/2 | 1600 | 63.0 | 183.0 mm | 42.5 |
| K- 07 25 10 23 | G 3/4 | 3000 | 85.0 | 240.5 mm | 58.0 |
| K- 07 25 10 24 | G 1 | 3000 | 85.0 | 240.5 mm | 58.0 |