

K-FI AK KOH PC-BEHAEL

MULTIFIX MINI

Activated carbon filters with polycarbonate bowl



Ieejas spiediens
Max. 16 bar
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
FA at P1 = 6 bar and pressure drop $\Delta p = 0.2$ bar
Blīvējums
NBR
Filtra ieliktnis
Activated carbon-POM
Korpuss
Die-cast zinc
Drain valve
Semi-automatic
Atlikusi eļļa
0.005 mg/m³
Caurplūdes vērtības mērijums
FA at P1 = 6 bar and pressure drop $\Delta p = 0.2$ bar

Apraksts

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 10 45	G 1/8	310	40.0	107.8 mm	12.3	95.5	5	0
K- 07 25 10 47	G 1/4	380	40.0	122.8 mm	12.3	110.5	5	0