

# K-FI AK KOH PC-BEHAEL S MULTIFIX

Activated carbon filters with polycarbonate bowl and bowl guard



Ieejas spiediens  
Max. 16 bar  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
FA at P1 = 6 bar and  $\Delta p = 0.2$  bar  
Blīvējums  
NBR  
Filtra ieliktnis  
Activated carbon-POM  
Korpuss  
Die-cast zinc  
Drain valve  
Semi-automatic  
Atlikusi eļļa  
0.005 mg/m<sup>3</sup>  
Caurplūdes vērtības mērijums  
FA at P1 = 6 bar and  $\Delta p = 0.2$  bar

## Apraksts

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 10 50	G 1/4	380	47.8	136.8 mm	27.0	109.8	6	1
K- 07 25 10 53	G 1/2	1500	68.8	167.0 mm	34.5	132.5	15	2