

K-FI METALLBEHAELTER SICHT MULTIFIX

Filters with metal bowl and sight glass



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar
Poru attālums filtra elementā
5 μm (BG 1 / BG 2), 40 μm (BG 3)
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Drain valve
Semi-automatic
Caurplūdes vērtības mērijums
At P1 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Centrifugal separator with a sintered filter element.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 47	G 1/4	2100	47.8	152.5 mm	27.0	125.5	6	1
K- 07 25 00 50	G 3/8	2100	47.8	152.5 mm	27.0	125.5	10	1
K- 07 25 00 53	G 1/2	4000	68.8	183.7 mm	34.5	149.2	15	2
K- 07 25 00 56	G 3/4	4000	68.8	183.7 mm	34.5	149.2	20	2
K- 07 25 00 59	G 1	8000	100.0	307.7 mm	52.0	255.7	25	3