

K-FI MIKRO PC-BEHAEL SCHU VARIOBLOC

Micro-filters with polycarbonate bowl and bowl guard



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 7 bar and pressure drop $\Delta p = 0,1$ bar
Filtra smalkums
0.01 μm
Gaisa kvalitāte ISO 85731
Class 1 dirt, class 1 oil
Iedarbības pakāpe
99.999 %
Caurplūdes vērtības mērijums
At P1 = 7 bar and pressure drop $\Delta p = 0,1$ bar

Apraksts

Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital. As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 μm).

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Filtra smalkums μm	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm
K- 07 25 22 96	0.01	G 1/4	370	48.0	155.0 mm	22.0
K- 07 25 22 95	0.01	G 3/8	420	48.0	155.0 mm	22.0
K- 07 25 22 94	0.01	G 1/2	1000	70.0	202.0 mm	26.0
K- 07 25 22 93	0.01	G 3/4	1100	70.0	202.0 mm	26.0
K- 07 25 22 92	0.01	G 1	1100	124.0	202.0 mm	26.0