

# K-FI PC-BEHAELTER H ABLV HW

## G

Filters with polycarbonate bowl, bowl guard and »HW« mounting bracket, semi-automatic drain valve



Ieejas spiediens  
Max. 10 bar  
Vides temperatūra  
Max. 70 °C  
Vielas temperatūra  
max. 70 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Darba spiediens  
1.5 - 9 bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu$ m  
Korpuss  
Die-cast aluminium  
Drain valve  
Semi- or fully-automatic  
Caurplūdes vērtības mērijums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Produkts

Apzīmējums	Vitnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	Tipizmērs
K- 07 25 06 35	G 1/4	1550	51.0	164.0 mm	21.0	143.0	1
K- 07 25 06 37	G 3/8	1800	51.0	164.0 mm	21.0	143.0	1
K- 07 25 06 39	G 1/2	1800	51.0	164.0 mm	21.0	143.0	1
K- 07 25 06 41	G 3/8	4900	68.0	191.5 mm	25.0	166.5	2
K- 07 25 06 43	G 1/2	4900	68.0	191.5 mm	25.0	166.5	2