



Ieejas spiediens
1.5 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar
Filtra smalkums
5.00 μm
Blīvējums
NBR
Aizsarggrozs
Polyamide
Filtra elements
Cellpor (PE)
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock)
Caurplūdes vērtības mērījums
At P2 = 6 bar, pressure drop $\Delta p = 1$ bar

Apraksts

Filters with excellent flow rates in modern design.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Filtra smalkums μm	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Tipizmērs	Kondensāta notece
K- 07 25 05 64	5.00	G 1/4	2000	52.0	164.0 mm	34.0	1	Semi
K- 07 25 05 65	5.00	G 3/8	2000	52.0	164.0 mm	34.0	1	Semi
K- 07 25 05 66	5.00	G 3/8	3500	63.0	189.5 mm	42.5	2	Semi
K- 07 25 05 67	5.00	G 1/2	3500	63.0	189.5 mm	42.5	2	Semi
K- 07 25 05 60	5.00	G 3/4	9000	85.0	250.0 mm	58.0	4	Semi
K- 07 25 05 61	5.00	G 1	9000	85.0	250.0 mm	58.0	4	Semi
K- 07 25 05 68	5.00	G 1/4	2000	52.0	181.0 mm	34.0	1	Auto
K- 07 25 05 69	5.00	G 3/8	2000	52.0	181.0 mm	34.0	1	Auto
K- 07 25 05 70	5.00	G 3/8	3500	63.0	206.0 mm	42.5	2	Auto
K- 07 25 05 71	5.00	G 1/2	3500	63.0	206.0 mm	42.5	2	Auto
K- 07 25 05 62	5.00	G 3/4	9000	85.0	264.0 mm	58.0	4	Auto
K- 07 25 05 63	5.00	G 1	9000	85.0	264.0 mm	58.0	4	Auto