

# K-FI PC-BEHAELTER SCHUTZK MULTIFIX

Filters with polycarbonate bowl and bowl guard



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Poru attālums filtra elementā  
5  $\mu\text{m}$  (BG 1 / BG 2), 40  $\mu\text{m}$  (BG 3)  
Korpuss  
Die-cast zinc, Aluminium for G 1 variant  
Drain valve  
Semi-automatic  
Caurplūdes vērtības mērijums  
At P1 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Centrifugal separator with a sintered filter element.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 48	G 1/4	2100	47.8	152.1 mm	27.0	125.1	6	1
K- 07 25 00 51	G 3/8	2100	47.8	152.1 mm	27.0	125.1	10	1
K- 07 25 00 54	G 1/2	4000	68.8	181.8 mm	34.5	147.3	15	2
K- 07 25 00 57	G 3/4	4000	68.8	181.8 mm	34.5	147.3	20	2
K- 07 25 00 60	G 1	8000	100.0	305.8 mm	52.0	253.8	25	3