

K-FI PC-BEHAELTER V ABLV HW

G

Filters with polycarbonate bowl, bowl guard and »HW« mounting bracket, fully-automatic drain valve



Ieejas spiediens
Max. 10 bar
Vides temperatūra
Max. 70 °C
Vielas temperatūra
max. 70 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Darba spiediens
1.5 - 9 bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm
Korpuss
Die-cast aluminium
Drain valve
Semi- or fully-automatic
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Produkts

Apzīmējums	Vitnes	Caurpl_de nom. l/min	A mm	B	C mm	D mm	Tipizmērs
K- 07 25 06 36	G 1/4	1550	51.0	164.0 mm	21.0	143.0	1
K- 07 25 06 38	G 3/8	1800	51.0	164.0 mm	21.0	143.0	1
K- 07 25 06 40	G 1/2	1800	51.0	164.0 mm	21.0	143.0	1
K- 07 25 06 42	G 3/8	4900	68.0	191.5 mm	25.0	166.5	2
K- 07 25 06 44	G 1/2	4900	68.0	191.5 mm	25.0	166.5	2