

K-FI REGL PC-BEHAELTER S MAN VARI0B

Filter regulators with polycarbonate bowl, bowl guard and pressure gauge



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Vielas temperatūra
max. 50 °C
Caurplūde
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
40 μm
Korpuss
Die-cast zinc
Membrāna
NBR
Atsperes korpuss
POM
Drain valve
Manual
Caurplūdes vērtības mērijums
At P1 = 10 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the knob down. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurplūde nom. l/min	A mm	B	C mm
K- 07 25 23 01	G 1/4	0.5 - 10 bar	2000	48.0	203,0 mm	68.0
K- 07 25 23 00	G 3/8	0.5 - 10 bar	3000	48.0	203,0 mm	68.0
K- 07 25 22 99	G 1/2	0.5 - 10 bar	5500	70.0	273,0 mm	98.0
K- 07 25 22 98	G 3/4	0.5 - 10 bar	6500	70.0	273,0 mm	98.0
K- 07 25 22 97	G 1	0.5 - 10 bar	6500	124.0	273,0 mm	98.0