

# K-FI RUECKSPUEL M

## DRUCKREGLER

Back-flushing filters with pressure regulator



Ieejas spiediens  
Max. 16 bar  
Vides temperatūra  
+5 °C to +40 °C  
Ūdens temperatūra maks.  
30 °C  
Ūdens temperatūra min.  
5 °C  
Poru attālums filtra elementā  
90 µm (first filter element), 110 µm (second filter element)  
Korpuss  
Brass  
Sietiņš  
Impact-resistant plastic

## Apraksts

Combined station for filtering and regulating the pressure of drinking and domestic water in addition to well, process and cooling water for once-through cooling systems, consisting of a diaphragm pressure regulator with a pressure-reduced single-seated valve and a back-flushing filter. The filter candle must be cleaned manually at regular intervals by back-flushing (flushing out dirt particles). Integrated back-flushing element with suction elements, back-flushing lever, wing lever for back-flushing element, hose connection for flushing water.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Ūdens temperatūra maks. °C	Ūdens temperatūra min. °C	Vītnes	Regulēšanas diapazons	Caurplūdes plūsmas koeficients m <sup>3</sup> /h	A mm	B	C m
K- 07 25 10 11	30	5	R 3/4	2 - 6 bar	3.0	79.7	213.0 mm	392.0
K- 07 25 10 12	30	5	R 1	2 - 6 bar	3.5	79.7	213.0 mm	392.0
K- 07 25 10 13	30	5	R 1 1/4	2 - 6 bar	4.0	79.7	213.0 mm	392.0