



Ieejas spiediens
Max. 16 bar
Vides temperatūra
+5 °C to +40 °C
Ūdens temperatūra maks.
30 °C
Ūdens temperatūra min.
5 °C
Poru attālums filtra elementā
90 µm (first filter element), 110 µm (second filter element)
Korpuss
Brass
Sietiņš
Impact-resistant plastic

Apraksts

For filtering drinking and domestic water in addition to well, process and cooling water for once-through cooling systems. These filters protect the water pipes and all water-carrying parts of the system on the downstream side against malfunctions and corrosion damage. The filter candle must be cleaned manually at regular intervals by back-flushing (flushing out dirt particles). Integrated back-flushing element with suction elements, back-flushing lever, wing lever for back-flushing element, hose connection for flushing water.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ūdens temperatūra maks. °C	Ūdens temperatūra min. °C	Vītnes	Caurplūdes plūsmas koeficients m ³ /h	A mm	B	C mm	DN
K- 07 25 10 08	30	5	R 3/4	3.0	80.0	184.0 mm	352.5	20
K- 07 25 10 09	30	5	R 1	3.5	80.0	184.0 mm	352.5	25
K- 07 25 10 10	30	5	R 1 1/4	4.0	106.4	228.0 mm	352.5	32