

K-FI SPEZI METALLBEHAEL M STANDAD

Special filters with metal bowl and manual drain valve



Ieejas spiediens
Max. 16 bar (polycarbonate bowl / bowl guard), Max. 25 bar (metal bowl)
Vides temperatūra
Max. 50 °C
Vielas temperatūra
max. 50 °C
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Iedarbības pakāpe
99.999 %
Poru attālums filtra elementā
0.01 μm
Korpuss
Die-cast zinc, painted silver
Caurplūdes vērtības mērijums
At P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	C mm	D mm	H mm	DN
K- 07 25 10 74	G 1/4	380	48.0	14.0	133.5	38.0	6
K- 07 25 10 77	G 3/8	380	48.0	14.0	133.5	38.0	6
K- 07 25 10 79	G 3/8	720	70.0	16.0	159.0	50.0	10
K- 07 25 10 81	G 1/2	1250	79.0	18.0	171.0	50.0	15
K- 07 25 10 84	G 3/4	7000	133.0	36.0	206.0	134.0	20
K- 07 25 10 87	G 1	7000	133.0	36.0	206.0	120.0	25