

Micro-filters (fine filters)



Ieejas spiediens
1.5 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar
Filtra smalkums
0.01 μm
Aizsarggrozs
Polyamide
Filtra elements
Borosilicate glass fibre
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock)
Putekļu filtrēšana
Class 1 acc. to DIN ISO 8753-1
Caurplūdes vērtības mērījums
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar

Apraksts

Micro-filters in modern design for compliance with strict compressed air purity requirements. Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 μm from compressed air and gases.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Filtra smalkums μm | Vītnes | Caurpl_de nom. l/min | A mm | B | C mm | Kondensāta notece |
|----------------|----------------------------------|--------|-------------------------|---------|----------|---------|-------------------|
| K- 07 25 10 33 | 0.01 | G 1/4 | 350 | 52.0 | 169.5 mm | 39.5 | Semi |
| K- 07 25 10 34 | 0.01 | G 3/8 | 350 | 52.0 | 169.5 mm | 39.5 | Semi |
| K- 07 25 10 35 | 0.01 | G 3/8 | 450 | 63.0 | 195.0 mm | 47.8 | Semi |
| K- 07 25 10 36 | 0.01 | G 1/2 | 450 | 63.0 | 195.0 mm | 47.8 | Semi |
| K- 07 25 10 19 | 0.01 | G 3/4 | 1500 | 85.0 | 255.0 mm | 63.0 | Semi |
| K- 07 25 10 20 | 0.01 | G 1 | 1500 | 85.0 | 255.0 mm | 63.0 | Semi |
| K- 07 25 10 37 | 0.01 | G 1/4 | 350 | 52.0 | 186.5 mm | 39.5 | Auto |
| K- 07 25 10 38 | 0.01 | G 3/8 | 350 | 52.0 | 186.5 mm | 39.5 | Auto |
| K- 07 25 10 39 | 0.01 | G 3/8 | 450 | 63.0 | 210.5 mm | 47.8 | Auto |
| K- 07 25 10 40 | 0.01 | G 1/2 | 450 | 63.0 | 210.5 mm | 47.8 | Auto |
| K- 07 25 10 21 | 0.01 | G 3/4 | 1500 | 85.0 | 269.0 mm | 63.0 | Auto |
| K- 07 25 10 22 | 0.01 | G 1 | 1500 | 85.0 | 269.0 mm | 63.0 | Auto |