

Micro-filters (fine filters)



Ieejas spiediens
1.5 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar
Filtra smalkums
0.01 μm
Aizsarggrozs
Polyamide
Filtra elements
Borosilicate glass fibre
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock)
Putekļu filtrēšana
Class 1 acc. to DIN ISO 8753-1
Caurplūdes vērtības mērījums
At P2 = 6 bar and pressure drop $\Delta p = 0.5$ bar

Apraksts

Micro-filters in modern design for compliance with strict compressed air purity requirements. Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 μm from compressed air and gases.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Filtra smalkums μm	Vītnes	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 10 33	0.01	G 1/4	350	52.0	169.5 mm	39.5	Semi
K- 07 25 10 34	0.01	G 3/8	350	52.0	169.5 mm	39.5	Semi
K- 07 25 10 35	0.01	G 3/8	450	63.0	195.0 mm	47.8	Semi
K- 07 25 10 36	0.01	G 1/2	450	63.0	195.0 mm	47.8	Semi
K- 07 25 10 19	0.01	G 3/4	1500	85.0	255.0 mm	63.0	Semi
K- 07 25 10 20	0.01	G 1	1500	85.0	255.0 mm	63.0	Semi
K- 07 25 10 37	0.01	G 1/4	350	52.0	186.5 mm	39.5	Auto
K- 07 25 10 38	0.01	G 3/8	350	52.0	186.5 mm	39.5	Auto
K- 07 25 10 39	0.01	G 3/8	450	63.0	210.5 mm	47.8	Auto
K- 07 25 10 40	0.01	G 1/2	450	63.0	210.5 mm	47.8	Auto
K- 07 25 10 21	0.01	G 3/4	1500	85.0	269.0 mm	63.0	Auto
K- 07 25 10 22	0.01	G 1	1500	85.0	269.0 mm	63.0	Auto