

Micro-filters (fine filters)



Ieejas spiediens  
1.5 - 16 bar  
Temperatūras diapazons  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Caurplūde  
At P2 = 6 bar and pressure drop  $\Delta p = 0.5$  bar  
Filtra smalkums  
0.01  $\mu\text{m}$   
Aizsarggrozs  
Polyamide  
Filtra elements  
Borosilicate glass fibre  
Korpuss  
Material: Grivory® (PA 66)  
Pieslēguma vītne  
Material: Die-cast zinc  
Tvertne  
Polycarbonate (with bayonet lock)  
Putekļu filtrēšana  
Class 1 acc. to DIN ISO 8753-1  
Caurplūdes vērtības mērījums  
At P2 = 6 bar and pressure drop  $\Delta p = 0.5$  bar

## Apraksts

Micro-filters in modern design for compliance with strict compressed air purity requirements. Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01  $\mu\text{m}$  from compressed air and gases.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Filtra smalkums $\mu\text{m}$	Vītne	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 10 33	0.01	G 1/4	350	52.0	169.5 mm	39.5	Semi
K- 07 25 10 34	0.01	G 3/8	350	52.0	169.5 mm	39.5	Semi
K- 07 25 10 35	0.01	G 3/8	450	63.0	195.0 mm	47.8	Semi
K- 07 25 10 36	0.01	G 1/2	450	63.0	195.0 mm	47.8	Semi
K- 07 25 10 19	0.01	G 3/4	1500	85.0	255.0 mm	63.0	Semi
K- 07 25 10 20	0.01	G 1	1500	85.0	255.0 mm	63.0	Semi
K- 07 25 10 37	0.01	G 1/4	350	52.0	186.5 mm	39.5	Auto
K- 07 25 10 38	0.01	G 3/8	350	52.0	186.5 mm	39.5	Auto
K- 07 25 10 39	0.01	G 3/8	450	63.0	210.5 mm	47.8	Auto
K- 07 25 10 40	0.01	G 1/2	450	63.0	210.5 mm	47.8	Auto
K- 07 25 10 21	0.01	G 3/4	1500	85.0	269.0 mm	63.0	Auto
K- 07 25 10 22	0.01	G 1	1500	85.0	269.0 mm	63.0	Auto