

Pre-filters



Ieejas spiediens
1.5 - 16 bar
Temperatūras diapazons
-10 °C to +50 °C
Darba vides
Saspiests gaiss
Caurplūde
At P2 = 6 bar, pressure drop $\Delta p = 0.5$ bar
Filtra smalkums
0.30 μm
Aizsarggrozs
Polyamide
Filtra elements
Impregnated paper
Korpuss
Material: Grivory® (PA 66)
Pieslēguma vītne
Material: Die-cast zinc
Tvertne
Polycarbonate (with bayonet lock)
Caurplūdes vērtības mērijums
At P2 = 6 bar, pressure drop $\Delta p = 0.5$ bar

Apraksts

Pre-filters in modern design for compliance with strict compressed air purity requirements. Pre-filters are used to separate solid impurities up to 0.3 μm from compressed air and gases.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Filtra smalkums μm	Vītne	Caurpl_de nom. l/min	A mm	B	C mm	Kondensāta notece
K- 07 25 10 25	0.30	G 1/4	500	52.0	169.5 mm	39.5	Semi
K- 07 25 10 26	0.30	G 3/8	500	52.0	169.5 mm	39.5	Semi
K- 07 25 10 27	0.30	G 3/8	750	63.0	195.0 mm	47.8	Semi
K- 07 25 10 28	0.30	G 1/2	750	63.0	195.0 mm	47.8	Semi
K- 07 25 10 15	0.30	G 3/4	2000	85.0	255.0 mm	63.0	Semi
K- 07 25 10 16	0.30	G 1	2000	85.0	255.0 mm	63.0	Semi
K- 07 25 10 29	0.30	G 1/4	500	52.0	186.5 mm	39.5	Auto
K- 07 25 10 30	0.30	G 3/8	500	52.0	186.5 mm	39.5	Auto
K- 07 25 10 31	0.30	G 3/8	750	63.0	210.5 mm	47.8	Auto
K- 07 25 10 32	0.30	G 1/2	750	63.0	210.5 mm	47.8	Auto
K- 07 25 10 17	0.30	G 3/4	2000	85.0	269.0 mm	63.0	Auto
K- 07 25 10 18	0.30	G 1	2000	85.0	269.0 mm	63.0	Auto