

# K-FI REG MANO HANSA PRO

# HANSA FLEX

Filter regulator, HANSA PRO2 with manual/semi-automatic condensate drain and pressure gauge, HANSA PRO

OFICIĀLĀ LATVIJAS PĀRSTĀVniecība



Modelis  
Diaphragm pressure regulator with relieving, centrifugal filter  
Vides temperatūra  
-10 °C to +50 °C  
Vielas temperatūra  
-10 °C to +50 °C  
Darba vides  
Saspiests gaiss  
Filtra smalkums  
5.00 µm  
maks. kondensāta daudzums  
49 cm<sup>3</sup>  
Manometra pieslēgums  
G 1/4 i  
Nominālā caurplūde G 1/2  
5.200 l/min (P1 = 10 bar, P2 = 6,3 bar/Delta P = 1 bar)  
PE maks. 4  
Pa 0,5 - 8 bar (Standard)&lt;BR&gt;Pa 0,1 - 1 bar&lt;BR&gt;Pa 0,1 - 2 bar&lt;BR&gt;Pa 0,2 - 4 bar&lt;BR&gt;Pa 0,5 - 10 bar&lt;BR&gt;Pa 0,5 - 16 bar  
PE maks. 6  
16 bar  
Nominālā caurplūde G 3/8  
4.300 l/min (P1 = 10 bar, P2 = 6,3 bar/Delta P = 1 bar)  
Stiprinājuma veids  
Line mounting, panel mounting, mounting kit or wall mounting  
Uzstādīšanas stāvoklis  
Vertical, drain down  
Vadība/drošinātājs  
lockable handwheel  
Filtra elements  
Cellpor  
Korpuss  
PA66  
Membrāna, blīvējumi  
Ms/NBR/PA6

## Produkts

Apzīmējums	Filtra smalkums µm	PE maks. 6 bar	Savienojums	Regulēšanas diapazons	Indikācijas diapazoni	Tvertne	Tipizmērs	Kondensāts
K- 07 25 21 60	5.00	16	G 3/8 female	0.1 - 1 bar	0 - 1,6 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 61	5.00	16	G 3/8 female	0.1 - 2 bar	0 - 2,5 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 62	5.00	16	G 3/8 female	0.2 - 4 bar	0 - 6 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 63	5.00	16	G 3/8 female	0.5 - 8 bar	0 - 10 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 64	5.00	16	G 3/8 female	0.5 - 10 bar	0 - 16 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 65	5.00	16	G 3/8 female	0.5 - 16 bar	0 - 25 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 66	5.00	16	G 1/2 female	0.1 - 1 bar	0 - 1,6 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 67	5.00	16	G 1/2 female	0.1 - 2 bar	0 - 2,5 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 68	5.00	16	G 1/2 female	0.2 - 4 bar	0 - 6 bar	polycarbonate with protective cage	2	manual / automatic
K- 07 25 21 69	5.00	16	G 1/2 female	0.5 - 8 bar	0 - 10 bar	polycarbonate with protective cage	2	manual / automatic

Apzīmējums	Filtra smalkums µm	PE maks. 6 bar	Savienojums	Regulēšanas diapazons	Indikācijas diapazoni	Tvertne	Tipizmērs	Kondensāt
K- 07 25 21 70	5.00	16	G 1/2 female	0.5 - 10 bar	0 - 16 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 71	5.00	16	G 1/2 female	0.5 - 16 bar	0 - 25 bar	polycarbonate with protective cage	2	manual / s automatic
K- 07 25 21 72	5.00	16	G 3/8 female	0.1 - 1 bar	0 - 1,6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 73	5.00	16	G 3/8 female	0.1 - 2 bar	0 - 2,5 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 74	5.00	16	G 3/8 female	0.2 - 4 bar	0 - 6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 75	5.00	16	G 3/8 female	0.5 - 8 bar	0 - 10 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 76	5.00	16	G 3/8 female	0.5 - 10 bar	0 - 16 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 77	5.00	16	G 3/8 female	0.5 - 16 bar	0 - 25 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 78	5.00	16	G 1/2 female	0.1 - 1 bar	0 - 1,6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 79	5.00	16	G 1/2 female	0.1 - 2 bar	0 - 2,5 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 80	5.00	16	G 1/2 female	0.2 - 4 bar	0 - 6 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 81	5.00	16	G 1/2 female	0.5 - 8 bar	0 - 10 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 82	5.00	16	G 1/2 female	0.5 - 10 bar	0 - 16 bar	zinc with visual display	2	manual / s automatic
K- 07 25 21 83	5.00	16	G 1/2 female	0.5 - 16 bar	0 - 25 bar	zinc with visual display	2	manual / s automatic