

# K-FI REGL METALLBE MANO STANDARD-MI

Filter regulators with metal bowl, incl. pressure gauge and panel nut



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5 µm  
Atsperes korpuss  
POM-brass  
Korpuss  
Die-cast zinc, painted silver  
Drain valve  
Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Caurpl\_de nom.  
350 l/min

## Apraksts

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. &lt;br&gt;The pressure setting can be locked by pushing the knob down.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	A mm	B	C mm	D mm	DN
K- 07 25 06 65	G 1/8	0.5 - 10 bar	40.0	163.5 mm	65.0	98.5	5
K- 07 25 06 66	G 1/4	0.5 - 10 bar	40.0	163.5 mm	65.0	98.5	5