

K-FI REGL METALLBEHAE M ABLV STANDA

Filter regulators with metal bowl and manual drain valve



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)
Regulēšanas diapazons
0.5 to 10 bar (polycarbonate bowl), 0.5 to 16 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (Size 1 / Size 3), 40 μm (Size 2 / Size 4)
Korpuss
Die-cast zinc (G1/4 to G1/2), silver painted; aluminium (G3/4 to G1), silver painted
Caurplūdes vērtības mērijums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	C mm	D mm	DN	F mm
K- 07 25 06 69	G 1/4	900	54.0	106.5	133.5	8	62.0
K- 07 25 06 72	G 3/8	900	54.0	106.5	133.5	8	62.0
K- 07 25 06 75	G 3/8	1500	70.0	120.5	161.0	11	76.5
K- 07 25 06 77	G 1/2	3000	82.0	130.0	172.0	14	83.0
K- 07 25 06 80	G 3/4	7000	125.0	190.6	264.0	25	145.0
K- 07 25 06 83	G 1	7000	125.0	190.6	264.0	25	145.0