

K-FI REGL METALLBEHAE MANO MULTIF M

Filter regulators with metal bowl and pressure gauge



Ieejas spiediens
Max. 16 bar (also for metal tank!)

Vides temperatūra
Max. 60 °C

Vielas temperatūra
max. 60 °C

Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Blīvējums
NBR

Poru attālums filtra elementā
5 μm

Atsperes korpuss
POM-brass

Korpuss
Die-cast zinc

Drain valve
Semi-automatic

Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmērs
K- 07 25 00 61	G 1/8	0.5 - 10 bar	950	40.0	162.0 mm	63.0	99.0	5	0
K- 07 25 00 64	G 1/4	0.5 - 10 bar	1100	40.0	162.0 mm	63.0	99.0	5	0