

# K-FI REGL PC-BEHAEL H ABLV STANDARD

Filter regulators with polycarbonate bowl and semi-automatic drain valve



Ieejas spiediens  
Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)  
Regulēšanas diapazons  
0.5 to 10 bar (polycarbonate bowl), 0.5 to 16 bar (metal bowl)  
Vides temperatūra  
Max. 60 °C  
Vielas temperatūra  
max. 60 °C  
Caurplūde  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar  
Blīvējums  
NBR  
Poru attālums filtra elementā  
5  $\mu\text{m}$  (Size 1 / Size 3), 40  $\mu\text{m}$  (Size 2 / Size 4)  
Korpuss  
Die-cast zinc (G1/4 to G1/2), silver painted; aluminium (G3/4 to G1), silver painted  
Caurplūdes vērtības mērījums  
At P1 = 8 bar, P2 = 6 bar and pressure drop  $\Delta p = 1$  bar

## Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Caurpl_de nom. l/min	A mm	C mm	D mm	DN	F mm
K- 07 25 06 67	G 1/4	900	54.0	106.5	129.7	8	62.0
K- 07 25 06 70	G 3/8	900	54.0	106.5	129.7	8	62.0
K- 07 25 06 73	G 3/8	1500	70.0	120.5	145.9	11	76.5
K- 07 25 06 76	G 1/2	3000	82.0	130.0	169.4	14	83.0
K- 07 25 06 79	G 3/4	7000	125.0	190.6	261.4	25	145.0
K- 07 25 06 82	G 1	7000	125.0	190.6	261.4	25	145.0