

K-FI REGL PC-BEHAEL MANO MULTIFIX M

Filter regulators with polycarbonate bowl and pressure gauge



Ieejas spiediens
Max. 16 bar (also for metal tank!)

Vides temperatūra
Max. 60 °C

Vielas temperatūra
max. 60 °C

Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Blīvējums
NBR

Poru attālums filtra elementā
5 μm

Atsperes korpuss
POM-brass

Korpuss
Die-cast zinc

Drain valve
Semi-automatic

Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Regulēšanas diapazons | Caurpl_de nom. l/min | A mm | B | C mm | D mm | DN | Tipizmērs |
|----------------|--------|-----------------------|-------------------------|---------|----------|---------|---------|----|-----------|
| K- 07 25 00 63 | G 1/8 | 0.1 - 3 bar | 950 | 40.0 | 165.5 mm | 63.0 | 102.5 | 5 | 0 |
| K- 07 25 00 62 | G 1/8 | 0.5 - 10 bar | 950 | 40.0 | 165.5 mm | 63.0 | 102.5 | 5 | 0 |
| K- 07 25 00 65 | G 1/4 | 0.1 - 3 bar | 1100 | 40.0 | 165.5 mm | 63.0 | 102.5 | 5 | 0 |
| K- 07 25 00 66 | G 1/4 | 0.5 - 10 bar | 1100 | 40.0 | 165.5 mm | 63.0 | 102.5 | 5 | 0 |