

K-FI REGL PC-BEHAEL S MANO MULTIFIX

Filter regulators with polycarbonate bowl, bowl guard and pressure gauge



Ieejas spiediens
Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Vides temperatūra
Max. 60 °C
Vielas temperatūra
max. 60 °C
Caurplūde
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar
Blīvējums
NBR
Poru attālums filtra elementā
5 μm (C55: 40 μm)
Atsperes korpuss
POM-brass
Korpuss
Die-cast zinc, Aluminium for G 1 variant
Drain valve
Semi-automatic
Caurplūdes vērtības mērījums
At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar

Apraksts

Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	Regulēšanas diapazons	Caurpl_de nom. l/min	A mm	B	C mm	D mm	DN	Tipizmers
K- 07 25 00 67	G 1/4	0.5 - 10 bar	1500	47.8	192.1 mm	67.0	125.1	6	1
K- 07 25 00 71	G 3/8	0.5 - 10 bar	1500	47.8	192.1 mm	67.0	125.1	10	1
K- 07 25 00 75	G 1/2	0.5 - 10 bar	3500	68.8	246.3 mm	99.0	147.3	15	2
K- 07 25 00 79	G 3/4	0.5 - 10 bar	3500	68.8	246.3 mm	99.0	147.3	20	2
K- 07 25 00 83	G 1	0.5 - 10 bar	12000	100.0	381.8 mm	128.0	253.8	25	3