

# K-FI AK KOH M DIFFERENZ MANO

Activated carbon filters with differential pressure gauge



Ieejas spiediens  
Min. 4 bar, Max. 16 bar  
Diferenciālā spiediena manometra indikāciju diapazons  
0 - 2 bar  
Korpuss, filtra tvertne  
Aluminium  
Vides temperatūra  
+5 °C to +60 °C  
Filtra ieliktnis  
Activated carbon  
Atlikusi eļļa  
0.005 mg/m<sup>3</sup>  
Caurplūdes vērtības mērījums  
At P1 = 6 bar and pressure drop  $\Delta p = 0.5\%$

## Apraksts

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	Caurpl_de nom. l/min	A mm	B1 mm	B2 mm	C mm	D mm
K- 07 25 13 18	G 1/4	500	82.5	318.5	245.0	57.0	263.0
K- 07 25 13 19	G 3/8	500	82.5	318.5	245.0	57.0	263.0
K- 07 25 13 20	G 1/2	500	82.5	318.5	245.0	57.0	263.0
K- 07 25 13 21	G 3/4	1000	82.5	388.5	315.0	57.0	403.0
K- 07 25 13 22	G 1	1500	118.0	403.5	330.0	72.0	368.0
K- 07 25 13 23	G 1 1/4	2650	118.0	503.5	430.0	72.0	568.0
K- 07 25 13 24	G 1 1/2	4150	118.0	603.5	530.0	72.0	768.0
K- 07 25 13 25	G 2	6650	118.0	793.5	720.0	72.0	1148.0