

# K-FI MIKRO M DIFFERENZ MANO

Micro-filters with differential pressure gauge



Ieejas spiediens  
Min. 4 bar, Max. 16 bar  
Diferenciālā spiediena manometra indikāciju diapazons  
0 - 2 bar  
Korpuss, filtra tvertne  
Aluminium  
Vides temperatūra  
+5 °C to +60 °C  
Filtra smalkums  
0.01 µm  
Iedarbības pakāpe  
99.9999 %  
Filtra ieliktnis  
Borosilicate (with glass-fibre and foam plastic)  
Caurplūdes vērtības mērijums  
At P1 = 6 bar and pressure drop  $\Delta p = 1.5\%$

## Apraksts

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Filtra smalkums µm	Vītnes	Caurpl_de nom. l/min	A mm	B1 mm	B2 mm	C mm	D mm
K- 07 25 13 02	0.01	G 1/4	1300	82.5	407.0	335.0	57.0	353.0
K- 07 25 13 03	0.01	G 3/8	1300	82.5	407.0	335.0	57.0	353.0
K- 07 25 13 04	0.01	G 1/2	1300	82.5	407.0	335.0	57.0	353.0
K- 07 25 13 05	0.01	G 3/4	2000	82.5	477.0	405.0	57.0	493.0
K- 07 25 13 06	0.01	G 1	4080	118.0	492.0	420.0	72.0	458.0
K- 07 25 13 07	0.01	G 1 1/4	4580	118.0	592.0	520.0	72.0	658.0
K- 07 25 13 08	0.01	G 1 1/2	6500	118.0	692.0	620.0	72.0	858.0
K- 07 25 13 09	0.01	G 2	9000	118.0	882.0	810.0	72.0	1238.0