

# K-FI MIKRO 0 DIFFERENZ MANO

Micro-filters without differential pressure gauge



Ieejas spiediens  
Min. 4 bar, Max. 16 bar  
Diferenciālā spiediena manometra indikāciju diapazons  
0 - 2 bar  
Korpuss, filtra tvertne  
Aluminium  
Vides temperatūra  
+5 °C to +60 °C  
Filtra smalkums  
0.01 µm  
Iedarbības pakāpe  
99.9999 %  
Filtra ieliktnis  
Borosilicate (with glass-fibre and foam plastic)  
Caurplūdes vērtības mērijums  
At P1 = 6 bar and pressure drop  $\Delta p = 1.5\%$

## Apraksts

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Filtra smalkums µm	Vītnes	Caurpl_de nom. l/min	A mm	B2 mm	C mm	D mm
K- 07 25 13 10	0.01	G 1/4	1300	82.5	338.0	57.0	353.0
K- 07 25 13 11	0.01	G 3/8	1300	82.5	338.0	57.0	353.0
K- 07 25 13 12	0.01	G 1/2	1300	82.5	338.0	57.0	353.0
K- 07 25 13 13	0.01	G 3/4	2000	82.5	408.0	57.0	493.0
K- 07 25 13 14	0.01	G 1	4080	118.0	423.0	72.0	458.0
K- 07 25 13 15	0.01	G 1 1/4	4580	118.0	523.0	72.0	658.0
K- 07 25 13 16	0.01	G 1 1/2	6500	118.0	623.0	72.0	858.0
K- 07 25 13 17	0.01	G 2	9000	118.0	813.0	72.0	1238.0