



Konstrukcija  
Taisna  
Modelis  
Cetop kvadrātveida atloks  
Standarts  
CETOP RP 63H  
ISO 6164  
ISO 6164  
Materiāls  
S355J2G3 (ST52.3)  
Virsmas aizsardzība  
ieeļļošana ar melno eļļu

## Produkts

| Apzīmējums       | Spiediens PB<br>bar | Tipizmērs | A<br>mm | Ø B<br>mm | C<br>mm | D<br>mm | E<br>mm |
|------------------|---------------------|-----------|---------|-----------|---------|---------|---------|
| G VKS 38 ST 250  | 250                 | 3/8"      | 18      | 12.5      | 24.5    | 18.0    | 30      |
| G VKS 12 ST 250  | 250                 | 1/2"      | 22      | 15.0      | 30.2    | 24.0    | 30      |
| G VKS 34 ST 250  | 250                 | 3/4"      | 28      | 20.0      | 38.1    | 31.5    | 35      |
| G VKS 1 ST 250   | 250                 | 1"        | 35      | 25.0      | 44.4    | 38.0    | 40      |
| G VKS 114 ST 250 | 250                 | 1.1/4"    | 43      | 32.0      | 50.8    | 43.0    | 45      |
| G VKS 112 ST 250 | 250                 | 1.1/2"    | 50      | 38.0      | 60.3    | 50.0    | 50      |
| G VKS 2 ST 250   | 250                 | 2"        | 62      | 47.0      | 71.4    | 62.0    | 60      |
| G VKS 212 ST 250 | 250                 | 2.1/2"    | 76      | 58.0      | 87.2    | 76.0    | 70      |
| G VKS 3 ST 250   | 250                 | 3"        | 90      | 70.0      | 101.6   | 90.0    | 80      |
| G VKS 312 ST 250 | 250                 | 3.1/2"    | 102     | 80.0      | 119.0   | 102.0   | 90      |
| G VKS 4 ST 250   | 250                 | 4"        | 114     | 90.0      | 131.0   | 114.0   | 105     |

PN = nominālais spiediens PB = maks. ekspluatācijas spiediens

Sērija: LL = ļoti vieglā L = vieglā S = smagā