

K-2-BK V DURCHG 20-63 INFI

2/2-way ball valve Ø 20 mm - Ø 63 mm full bore



Darba vides
Compressed air, vacuum, inert gases
Eksploatācijas spiediens
-0,99 bar - 15 bar
Temperatūras diapazons
-20 °C to +80 °C
Blīvgredzens
NBR
Blīvējums
NBR
Drošības gredzens
Technopolymer
Korpuss
Nickel-plated brass
Spīlgredzens
Stainless steel 1.4301
Uzgrieznis
Nickel-plated brass

Produkts

Apzīmējums	Caurules ārējais Ø	B mm	C mm	DN	E mm	G mm	H mm	L mm	SW1 mm	SW2 mm
K- 07 40 54 36	20 mm	31.5	58.5	17	34.5	88	42.0	121.5	32	30
K- 07 40 54 37	25 mm	38.5	61.5	22	42.5	106	47.5	138.5	41	35
K- 07 40 54 38	32 mm	46.0	75.0	29	52.0	106	53.0	167.0	50	45
K- 07 40 54 39	40 mm	52.5	81.0	37	63.0	134	65.0	186.0	59	55
K- 07 40 54 40	50 mm	63.5	103.0	46	73.0	134	72.5	230.0	69	65