


Ball valves with wing lever, male/male thread



Pieteikums platība

Compressed air, water, non-toxic and neutral gases, heating oil (EL),(S), luibricants, dieseloil, water beased coatings

Ekspluatācijas temperatūra

-20 °C to +130 °C

Vitnes apraksts

G thread acc. to DIN EN ISO 228-1, R thread acc. to DIN EN 10226 (ISO 7-1)

Korpuss

Nickel-plated brass

Lode

hardchrome-plated brass

Lodes blīvējums

PTFE

Svira

Alu, painted black

Vārpstas blīvējums

PTFE (politetrafluoretilēns)

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	DN	PN (bar)	Vitnes	A mm	B mm	E mm	F mm	L mm	SW mm
K- 07 30 20 22	8	100	R 1/4	45.0	43.0	11.0	11.0	54.5	18
K- 07 30 20 23	10	100	R 3/8	45.0	51.0	11.2	11.2	66.0	21
K- 07 30 20 24	15	100	R 1/2	55.0	54.5	14.9	14.9	82.0	27
K- 07 30 20 25	20	100	R 3/4	55.0	66.0	16.1	16.1	94.0	33
K- 07 30 20 26	25	100	R 1	70.0	70.0	19.0	19.0	107.0	40