

Ball valves with hand lever, female/male thread



Pieteikums platība

Compressed air, water, non-toxic and neutral gases, heating oil (EL),(S), luibricants, dieseloil, water beased coatings

Ekspluatācijas temperatūra

-20 °C to +130 °C

Vitnes apraksts

G thread acc. to DIN EN ISO 228-1, R thread acc. to DIN EN 10226 (ISO 7-1)

Korpuss

Nickel-plated brass

Lode

hardchrome-plated brass

Lodes blīvējums

PTFE

Svira

Alu, painted black

Vārpstas blīvējums

PTFE (politetrafluoretilēns)

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	DN	PN (bar)	Vitnes	A mm	B mm	E mm	F mm	L mm	SW1 mm	SW2 mm
K- 07 30 00 17	8	80	G/R 1/4	75.0	51.5	11.0	7.0	49.0	18	18
K- 07 30 00 18	10	80	G/R 3/8	75.0	54.0	11.0	8.5	56.0	21	21
K- 07 30 00 19	15	80	G/R 1/2	100.0	64.0	14.9	8.5	68.0	26	27
K- 07 30 00 20	20	80	G/R 3/4	100.0	68.0	16.0	14.0	77.0	32	33
K- 07 30 00 21	25	80	G/R 1	120.0	80.0	19.0	15.0	89.0	39	40
K- 07 30 00 22	32	80	G/R 1 1/4	150.0	95.0	21.2	16.0	100.0	49	50
K- 07 30 00 23	40	80	G/R 1 1/2	150.0	103.0	21.2	18.0	114.5	56	57
K- 07 30 00 24	50	80	G/R 2	175.0	115.5	25.5	21.0	136.0	69	70