

K-PROP VENTIL LU GA WA 24 V DC

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVniecība

Proportional valves for controlling the flow of air / gas / water / oil, 24 VDC, closed when de-energised



Temperatūras diapazons
Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)
Darba vides
Air, neutral gases, water, oil
Spiediena diapazons
Vacuum (max. 8 bar)
Vadība
Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA
Drošinātāja rīcība
Tight closure in case of loss of voltage
Iekšējās daļas
Stainless steel
Korpuss, vārsta ligzda
Brass
Vārsta disks
FKM
Blīvējums
FKM

Apraksts

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital.
Proportional valves allow the medium to be varied as a function of an electronic input variable.
By linking these valves to the electronics, it is possible to improve their accuracy and broaden their range of applications. A pressure regulator, for instance, needs to be suitable for several pressure ranges without having to adjust the pressure manually.
Proportional valves control the output pressure in a closed control loop proportionally to the selected setpoint signal. This output pressure, in other words, is continually compared with the specified setpoint and automatically adjusted according to actual parameter values.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Savienojums | DN | maks. eksploatācijas spiediena atšķirība bar | A mm | B | C mm |
|----------------|-------------|----|---|---------|---------|---------|
| K- 07 25 09 89 | G 1/8" | 1 | 5 | 59.0 | 25.0 mm | 78.0 |
| K- 07 25 09 90 | G 1/8" | 2 | 4 | 59.0 | 25.0 mm | 78.0 |