


Safety ball valve with spring return



Ekspluatācijas temperatūra
-20 °C to +170 °C
Vītnes apraksts
Rp thread acc. to ISO 7-1
Atspere
Stainless steel 1.4301
Korpuss
Nickel-plated brass
Lode
hardchrome-plated brass
Lodes blīvējums
PTFE
Svira
Steel - PVC coated
Vārpstas blīvējums
FKM

Apraksts

2/2-way safety ball valves, two parts, made of nickel-plated brass with spring return. Applications: Compressed air, water, oils, fuel oil, fuels, inert gases. Silicone-free. The ball valve is closed in the normal position and opens against spring force.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | DN | PN (bar) | Vītnes | A mm | B mm | L mm |
|----------------|----|----------|----------|---------|---------|---------|
| K- 07 30 30 40 | 8 | 65 | Rp 1/4 | 100.0 | 40.0 | 50.0 |
| K- 07 30 30 43 | 10 | 65 | Rp 3/8 | 100.0 | 40.0 | 60.0 |
| K- 07 30 30 39 | 15 | 65 | Rp 1/2 | 100.0 | 43.0 | 75.0 |
| K- 07 30 30 42 | 20 | 40 | Rp 3/4 | 120.0 | 51.0 | 80.0 |
| K- 07 30 30 36 | 25 | 40 | Rp 1 | 120.0 | 55.0 | 90.0 |
| K- 07 30 30 38 | 32 | 40 | Rp 1 1/4 | 158.0 | 75.0 | 110.0 |
| K- 07 30 30 37 | 40 | 40 | Rp 1 1/2 | 158.0 | 81.0 | 120.0 |
| K- 07 30 30 41 | 50 | 40 | Rp 2 | 158.0 | 88.0 | 140.0 |