

K-S-BKR 0 ENTL ABSCHL

Safety ball valves, lockable, without relief port



Temperatūra

-40 ° C up to max. +170 ° C; Warning: The freezing fluid in the system may damage the valve difficult

Vītnes apraksts

Rp thread acc. to EN 10226

Korpuss

Nickel-plated brass

Lodes blīvējums

PTFE

Svira

Steel - PVC coated

Vārpstas blīvējums

PTFE (politetrafluoretilēns)

Apraksts

2/2-way safety ball valves made of nickel-plated brass. Specially designed for pneumatic applications. The ball valve can be locked manually. Full bore, heavy-duty type.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	DN	PN (bar)	Vītnes	A mm	B mm	L mm
K- 07 30 21 29	8	65	Rp 1/4	82.0	39.5	51.0
K- 07 30 21 30	10	65	Rp 3/8	82.0	39.5	51.0
K- 07 30 21 31	15	65	Rp 1/2	100.0	43.0	61.0
K- 07 30 21 32	20	40	Rp 3/4	120.0	52.5	74.5
K- 07 30 21 33	25	40	Rp 1	120.0	57.0	90.5
K- 07 30 21 34	32	30	Rp 1 1/4	158.0	78.0	104.0
K- 07 30 21 35	40	30	Rp 1 1/2	158.0	85.0	117.0
K- 07 30 21 36	50	30	Rp 2	158.0	92.0	135.0