

K-3 BKR T VA LEICHT

3-way ball valves, T-bore, lightweight type



Vielas temperatūra
-15 °C to max. +100 °C
Vītnes apraksts
Rp thread acc. to ISO 7-1
Atspere
Stainless-steel
Blīvējums
PTFE
Korpuss un lode
Nickel-plated brass
Svira
Aluminium, painted black

Apraksts

Sealing on all sides with T-bore. In contrast to the 1084 series, the lever of this model can only be turned 90° rather than 180°. Only two valve positions are therefore possible instead of four.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | DN | Vītnes | A mm | B mm | L mm | Lodes urbums | maks. ekspluatācijas spiediens pie 20 °C bar |
|----------------|----|----------|---------|---------|---------|--------------|---|
| K- 07 30 19 68 | 15 | Rp 1/2 | 130.0 | 85.0 | 80.0 | 13 | 40 |
| K- 07 30 19 69 | 20 | Rp 3/4 | 160.0 | 98.0 | 96.0 | 18 | 40 |
| K- 07 30 19 70 | 25 | Rp 1 | 160.0 | 102.0 | 113.0 | 23 | 25 |
| K- 07 30 19 71 | 32 | Rp 1 1/4 | 195.0 | 121.0 | 130.0 | 29 | 16 |
| K- 07 30 19 72 | 40 | Rp 1 1/2 | 195.0 | 125.0 | 147.0 | 35 | 16 |
| K- 07 30 19 73 | 50 | Rp 2 | 235.0 | 141.0 | 169.0 | 44 | 16 |