

K-3 BKR T VA LEICHT

3-way ball valves, T-bore, lightweight type



Vielas temperatūra
-15 °C to max. +100 °C
Vītnes apraksts
Rp thread acc. to ISO 7-1
Atspere
Stainless-steel
Blīvējums
PTFE
Korpuss un lode
Nickel-plated brass
Svira
Aluminium, painted black

Apraksts

Sealing on all sides with T-bore. In contrast to the 1084 series, the lever of this model can only be turned 90° rather than 180°. Only two valve positions are therefore possible instead of four.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	DN	Vītnes	A mm	B mm	L mm	Lodes urbums	maks. ekspluatācijas spiediens pie 20 °C bar
K- 07 30 19 68	15	Rp 1/2	130.0	85.0	80.0	13	40
K- 07 30 19 69	20	Rp 3/4	160.0	98.0	96.0	18	40
K- 07 30 19 70	25	Rp 1	160.0	102.0	113.0	23	25
K- 07 30 19 71	32	Rp 1 1/4	195.0	121.0	130.0	29	16
K- 07 30 19 72	40	Rp 1 1/2	195.0	125.0	147.0	35	16
K- 07 30 19 73	50	Rp 2	235.0	141.0	169.0	44	16