



Ekspluatācijas spiediens
Max. 40 bar
Ekspluatācijas temperatūra
-15 °C to +100 °C
Vītnes apraksts
G thread acc. DIN EN ISO 228-1
Korpuss
Nickel-plated brass (outside); Brass with a bare metal surface (inside)
Lode
Chrome-plated brass
Lodes blīvējums
PTFE
Rokrats
Plastic
Vārpstas blīvējums
NBR

Apraksts

Brass ball valves in the standard series with fine adjustment. Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line. The flow rate can be regulated extremely precisely as a result. The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	DN	Vītnes	A mm	B mm	L mm
K- 07 30 00 41	10	G 3/8	83.0	63.0	43.4
K- 07 30 00 42	15	G 1/2	83.0	70.0	50.1
K- 07 30 00 43	20	G 3/4	83.0	76.0	58.0
K- 07 30 00 44	25	G 1	83.0	80.0	68.8
K- 07 30 00 45	32	G 1 1/4	130.0	110.0	81.0
K- 07 30 00 46	40	G 1 1/2	130.0	116.0	93.2
K- 07 30 00 47	50	G 2	130.0	123.0	110.2