

K-3 BKR L DOPPELWIRKEND

Stainless steel ball valves, 3-way, with double-acting actuator, L-bore



Modelis

Pneumatic actuators, in double- or single acting version, with integrated end-position feedback

Urbums

L-veida

Ekspluatācijas spiediens

max. 63 bar (depending on temperature and nominal size)

Ekspluatācijas temperatūra

-20 °C to +70 °C

Griešanas leņķis

90 °

Normētas saskarnes

Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S

Regulēšanas spiediens

5.5 bar

Vārsta adapteris

Acc. to NAMUR

Lodveida krāna blīvējums

PTFE/FKM

Lodveida krāns

Stainless steel 1.4401, with ISO-flange plate

Piedzīņa

aluminium eloxed

Piedzīņas blīvējums

NBR

Apraksts

3-way cock, reduced bore

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Griešanas leņķis	DN	Vītnes	A mm	Stellung	B mm	D mm	L mm	SW mm
K- 07 30 02 93	90	15	Rp 1/2	116.0	L 1	130.0	20.0	73.0	27
K- 07 30 02 94	90	20	Rp 3/4	116.0	L 1	136.0	23.0	80.0	32
K- 07 30 02 95	90	25	Rp 1	133.0	L 1	148.5	28.5	90.0	41
K- 07 30 02 96	90	32	Rp 1 1/4	133.0	L 1	153.5	36.5	90.0	50
K- 07 30 02 97	90	40	Rp 1 1/2	137.0	L 1	173.0	37.0	105.0	55
K- 07 30 02 98	90	50	Rp 2	161.0	L 1	196.5	47.5	115.0	71