

K-3 BKR L EINFACHWIRKEND

Stainless steel ball valves, 3-way, with single-acting actuator, L-bore



Modelis

Pneumatic actuators, in double- or single acting version, with integrated end-position feedback

Urbums

L-veida

Ekspluatācijas spiediens

max. 63 bar (depending on temperature and nominal size)

Ekspluatācijas temperatūra

-20 °C to +70 °C

Griešanas leņķis

90 °

Normētas saskarnes

Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S

Regulēšanas spiediens

5.5 bar

Vārsta adapteris

Acc. to NAMUR

Lodveida krāna blīvējums

PTFE/FKM

Lodveida krāns

Stainless steel 1.4401, with ISO-flange plate

Piedziņa

aluminium eloxed

Piedziņas blīvējums

NBR

Apraksts

3-way cock, reduced bore

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Griešanas leņķis | DN | Vītnes | A mm | Stellung | B mm | D mm | L mm | SW mm |
|----------------|------------------|----|----------|---------|----------|---------|---------|---------|----------|
| K- 07 30 03 11 | 90 | 15 | Rp 1/2 | 133.0 | L 1 | 139.0 | 20.0 | 73.0 | 27 |
| K- 07 30 03 12 | 90 | 20 | Rp 3/4 | 137.0 | L 1 | 159.0 | 23.0 | 80.0 | 32 |
| K- 07 30 03 13 | 90 | 25 | Rp 1 | 161.0 | L 1 | 174.5 | 28.5 | 90.0 | 41 |
| K- 07 30 03 14 | 90 | 32 | Rp 1 1/4 | 161.0 | L 1 | 179.5 | 36.5 | 90.0 | 50 |
| K- 07 30 03 15 | 90 | 40 | Rp 1 1/2 | 180.0 | L 1 | 185.0 | 37.0 | 105.0 | 55 |
| K- 07 30 03 16 | 90 | 50 | Rp 2 | 209.0 | L 1 | 213.5 | 47.5 | 115.0 | 71 |