

# K-3 BKR L EINFACHWIRKEND

Stainless steel ball valves, 3-way, with single-acting actuator, L-bore



## Modelis

Pneumatic actuators, in double- or single acting version, with integrated end-position feedback

## Urbums

L-veida

Ekspluatācijas spiediens

max. 63 bar (depending on temperature and nominal size)

Ekspluatācijas temperatūra

-20 °C to +70 °C

Griešanas leņķis

90 °

Normētas saskarnes

Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S

Regulēšanas spiediens

5.5 bar

Vārsta adapteris

Acc. to NAMUR

Lodveida krāna blīvējums

PTFE/FKM

Lodveida krāns

Stainless steel 1.4401, with ISO-flange plate

Piedziņa

aluminium eloxed

Piedziņas blīvējums

NBR

## Apraksts

3-way cock, reduced bore

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Griešanas leņķis	DN	Vītnes	A mm	Stellung	B mm	D mm	L mm	SW mm
K- 07 30 03 11	90	15	Rp 1/2	133.0	L 1	139.0	20.0	73.0	27
K- 07 30 03 12	90	20	Rp 3/4	137.0	L 1	159.0	23.0	80.0	32
K- 07 30 03 13	90	25	Rp 1	161.0	L 1	174.5	28.5	90.0	41
K- 07 30 03 14	90	32	Rp 1 1/4	161.0	L 1	179.5	36.5	90.0	50
K- 07 30 03 15	90	40	Rp 1 1/2	180.0	L 1	185.0	37.0	105.0	55
K- 07 30 03 16	90	50	Rp 2	209.0	L 1	213.5	47.5	115.0	71