


K-SSVKM NW 5 SCHL TUE MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, with bulkhead fitting and hose stem

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVniecība



Ekspluatācijas spiediens
0 - 35 bar, maximum static working pressure (non-pulsating)
Vielas temperatūra
-20 °C to +100 °C
Korpuss, uzmava, vārsta korpuss
Brass
Atspere, sprostgredzens, lodes
Stainless steel
Blīvējums
NBR

Apraksts

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	Starpsienas vītnes	SW mm
K- 07 35 06 45	560	60.0	Stem, I.D. 4	M 10 x 1	14
K- 07 35 06 46	560	60.0	Stem, I.D. 6	M 12 x 1	17
K- 07 35 06 47	560	60.0	Stem, I.D. 9	M 12 x 1	17