

K-SVKM NW 5 SCHL TUE MS

BL1

Quick disconnect couplings DN 5, brass with a bare metal surface, with hose stem



Ekspluatācijas spiediens
0 - 35 bar, maximum static working pressure (non-pulsating)
Vielas temperatūra
-20 °C to +100 °C
Korpuss, uzmava, vārsta korpuss
Brass
Atspere, sprostgredzens, lodes
Stainless steel
Blīvējums
NBR

Apraksts

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Caurpl_de nom. l/min | Garums mm | Savienojums |
|----------------|-------------------------|--------------|--------------|
| K- 07 35 06 40 | 560 | 47.0 | Stem, I.D. 4 |
| K- 07 35 06 52 | 560 | 46.0 | Stem, I.D. 5 |
| K- 07 35 06 41 | 560 | 46.0 | Stem, I.D. 6 |
| K- 07 35 06 53 | 560 | 46.0 | Stem, I.D. 8 |
| K- 07 35 06 42 | 560 | 46.0 | Stem, I.D. 9 |