

K-SVKM NW 5 SCHL UEB MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, with swivel nut and kink protector spring

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVniecība



Ekspluatācijas spiediens
0 - 35 bar, maximum static working pressure (non-pulsating)
Vielas temperatūra
-20 °C to +100 °C
Korpuss, uzmava, vārsta korpuss
Brass
Atspere, sprostgredzens, lodes
Stainless steel
Blīvējums
NBR

Apraksts

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Modelis	Savienojums	SW mm
K- 07 35 06 48	560	120.0	Rigid	Hose connection 6 x 4	14
K- 07 35 06 49	560	132.0	Rigid	Hose connection 8 x 6	14
K- 07 35 06 50	560	134.0	Swivelling 360°	Hose connection 6 x 4	14
K- 07 35 06 51	560	145.0	Swivelling 360°	Hose connection 8 x 6	14