


# K-SVKM NW 7,2 SCHL-TUE MS BL CL

Quick disconnect couplings DN 7.2, brass with a bare metal surface, with hose stem



Ekspluatācijas spiediens  
0 - 35 bar, maximum static working pressure (non-pulsating)  
Vielas temperatūra  
-20 °C to +100 °C  
Korpuss, uzmava, vārsta korpuss  
Brass  
Blīvējums  
NBR  
Atspere, sprostgredzens, tapas  
Stainless steel

## Apraksts

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. Compatible with CEJN 320, Rectus 25/26 and JWL 520/530. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Garums mm	Savienojums
K- 07 35 07 45	54.0	Stem, I.D. 6
K- 07 35 07 46	54.0	Stem, I.D. 9
K- 07 35 07 47	53.5	Stem, I.D. 13
K- 07 35 07 48	54.0	Stem, I.D. 8
K- 07 35 07 49	54.0	Stem, I.D. 10