


# K-SVKM NW 7,2 SCHL-ANSCHL

## MS

Quick disconnect couplings DN 7.2, nickel-plated brass, with hose connector, with swivel nut



Ekspluatācijas spiediens  
0 - 35 bar, maximum static working pressure (non-pulsating)  
Vielas temperatūra  
-20 °C to +100 °C  
Korpuss uzmava  
Nickel-plated brass  
Vārsts  
Brass with a bare metal surface  
Atspere, sprostgredzens  
Stainless steel 1.4310  
Fiksācijas tapas  
Stainless steel 1.4034  
Blīvējums  
NBR

## Apraksts

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. <br>In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	SW mm
K- 07 35 12 67	1000	58.0	Hose connection 6 x 4	21
K- 07 35 07 24	1000	45.0	Hose connection 8 x 6	21
K- 07 35 07 25	1000	49.0	Hose connection 10 x 8	21
K- 07 35 07 26	1000	49.0	Hose connection 12 x 9	21