


K-SVKM NW 7,2 SCHL-ANSCHL

MS

Quick disconnect couplings DN 7.2, nickel-plated brass, with hose connector, with swivel nut



Ekspluatācijas spiediens
0 - 35 bar, maximum static working pressure (non-pulsating)
Vielas temperatūra
-20 °C to +100 °C
Korpuss uzmava
Nickel-plated brass
Vārsts
Brass with a bare metal surface
Atspere, sprostgredzens
Stainless steel 1.4310
Fiksācijas tapas
Stainless steel 1.4034
Blīvējums
NBR

Apraksts

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt.
In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Savienojums	SW mm
K- 07 35 12 67	1000	58.0	Hose connection 6 x 4	21
K- 07 35 07 24	1000	45.0	Hose connection 8 x 6	21
K- 07 35 07 25	1000	49.0	Hose connection 10 x 8	21
K- 07 35 07 26	1000	49.0	Hose connection 12 x 9	21