


# K-SVKM NW 7,8 SCHL TUE VA

Quick disconnect couplings DN 7.8, stainless steel 1.4305, with hose stem

**HANSA FLEX**  
OFICIĀLĀ LATVIJAS PĀRSTĀVniecība



Ekspluatācijas spiediens  
0 - 35 bar, maximum static working pressure (non-pulsating)  
Vielas temperatūra  
-15 °C to +200 °C  
Korpuss, uzmava, vārsta korpuss  
Stainless steel 1.4305  
Atspere, sprostgredzens, lodes  
Stainless steel  
Blīvējums  
FKM

## Apraksts

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. Ideal for: Pneumatic tools, laboratory equipment, chemical applications, instrumentation and control, safety systems, industrial plant engineering, mechanical engineering.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Caurpl_de nom.<br>l/min | Garums<br>mm | Savienojums   | SW<br>mm |
|----------------|-------------------------|--------------|---------------|----------|
| K- 07 35 07 96 | 1800                    | 73.5         | Stem, I.D. 6  | 19       |
| K- 07 35 07 97 | 1800                    | 73.5         | Stem, I.D. 8  | 19       |
| K- 07 35 07 98 | 1800                    | 73.5         | Stem, I.D. 9  | 19       |
| K- 07 35 07 99 | 1800                    | 73.5         | Stem, I.D. 10 | 19       |
| K- 07 35 08 00 | 1800                    | 73.5         | Stem, I.D. 13 | 19       |