



Ekspluatācijas spiediens  
0 - 35 bar, maximum static working pressure (non-pulsating)  
Vielas temperatūra  
-20 °C to +100 °C  
Atbloķēšanas uzdevums  
Anodised aluminium  
Atspere, sprostgredzens, lodes  
stain less steel  
Blīvējums  
NBR

## Apraksts

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Caurpl_de nom.<br>l/min | Garums<br>mm | Krāsa   | Savienojums  | SW<br>mm |
|----------------|-------------------------|--------------|---------|--------------|----------|
| K- 07 35 06 80 | 560                     | 45.0         | zaļš    | G 1/8 male   | 14       |
| K- 07 35 06 81 | 560                     | 47.0         | zaļš    | G 1/4 male   | 17       |
| K- 07 35 06 82 | 560                     | 45.0         | zaļš    | G 1/8 female | 14       |
| K- 07 35 06 83 | 560                     | 47.0         | zaļš    | G 1/4 female | 17       |
| K- 07 35 06 84 | 560                     | 45.0         | Brown   | G 1/8 male   | 14       |
| K- 07 35 06 85 | 560                     | 47.0         | Brown   | G 1/4 male   | 17       |
| K- 07 35 06 86 | 560                     | 45.0         | Brown   | G 1/8 female | 14       |
| K- 07 35 06 87 | 560                     | 47.0         | Brown   | G 1/4 female | 17       |
| K- 07 35 06 88 | 560                     | 45.0         | zils    | G 1/8 male   | 14       |
| K- 07 35 06 89 | 560                     | 47.0         | zils    | G 1/4 male   | 17       |
| K- 07 35 06 90 | 560                     | 45.0         | zils    | G 1/8 female | 14       |
| K- 07 35 06 91 | 560                     | 47.0         | zils    | G 1/4 female | 17       |
| K- 07 35 06 92 | 560                     | 45.0         | sarkans | G 1/8 male   | 14       |
| K- 07 35 06 93 | 560                     | 47.0         | sarkans | G 1/4 male   | 17       |
| K- 07 35 06 94 | 560                     | 45.0         | sarkans | G 1/8 female | 14       |
| K- 07 35 06 95 | 560                     | 47.0         | sarkans | G 1/4 female | 17       |