


# K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Ekspluatācijas spiediens  
0 - 35 bar, maximum static working pressure (non-pulsating)  
Korpuss  
Brass  
Vielas temperatūra  
-20 °C to +100 °C  
Vārsts  
Die-cast zinc, nickel-plated  
Atbloķēšanas uzmava  
Anodised aluminium  
Atspere, sprostgredzens, lodes  
stain less steel  
Blīvējums  
NBR



## Apraksts

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Caurpl_de nom. l/min	Garums mm	Krāsa	Savienojums	SW mm
K- 07 35 08 01	1800	57.5	zaļš	G 1/4 male	19
K- 07 35 08 02	1800	57.5	zaļš	G 3/8 male	19
K- 07 35 08 03	1800	55.5	zaļš	G 1/4 female	19
K- 07 35 08 04	1800	54.5	zaļš	G 3/8 female	19
K- 07 35 08 05	1800	57.5	Brown	G 1/4 male	19
K- 07 35 08 06	1800	57.5	Brown	G 3/8 male	19
K- 07 35 08 07	1800	55.5	Brown	G 1/4 female	19
K- 07 35 08 08	1800	54.5	Brown	G 3/8 female	19
K- 07 35 08 09	1800	57.5	zils	G 1/4 male	19
K- 07 35 08 10	1800	57.5	zils	G 3/8 male	19
K- 07 35 08 11	1800	55.5	zils	G 1/4 female	19
K- 07 35 08 12	1800	54.5	zils	G 3/8 female	19
K- 07 35 08 13	1800	57.5	sarkans	G 1/4 male	19
K- 07 35 08 14	1800	57.5	sarkans	G 3/8 male	19
K- 07 35 08 15	1800	55.5	sarkans	G 1/4 female	19
K- 07 35 08 16	1800	54.5	sarkans	G 3/8 female	19